



Down2Earth bvba
Corda Campus, Corda 5
Kempische Steenweg 301/9
3500 Hasselt - BELGIUM
VAT ID - BE 0898.388.858

Phone: +32 11 281 666
Mobile: +32 476 740 876
Fax: +32 11 281 667
info@down2earth.com
www.down2earth.com

Microtunneling bentonite autolubrication stations.

Bentonite autolubrication stations.

Injection station for automatic bentonite distribution with 1 central inlet and 3 outlets to bentonite injection ports in the product pipe. Alternatively one station can be used for different jacking pipes with only one or 2 bentonite injection ports

The pneumatic valves are electronically controlled from the control room or from a stand-alone control unit. One set consists of lubrication injection station, control cable and air supply line. Lubrication hoses, control cable, air supply line and fittings to / from the injection stations are local supply.

Offered lubrication station is compatible to those supplied by Herrenknecht AG.

Electro-pneumatic valve blocs	3 Pieces
Type inlet	DN24/28L
Number inlet	1
Type outlet	DN18/22L
Number outlets	3
Electrical panel for remote control	1
All mounted on robust steel frame	
Dimensions LxWxH (indicative)	750 x 400 x 300
Weight (indicative)	30 KG

New and serviced in stock.

Optionally the **autolubrication stations** can be equipped with **LED tunnellights** so that there is no separate power supply needed for the **tunnel lightning**.

For Sale & For Rent

