



Down2Earth bvba
 Corda Campus, Corda 5
 Kempische Steenweg 301/9
 3500 Hasselt - BELGIUM
 VAT ID - BE 0898.388.858

Phone: +32 11 281 666
Mobile: +32 476 740 876
Fax: +32 11 281 667
info@down2earth.com
www.down2earth.com

Microtunneling Bauer slurry separation plant BE170-60.

Bauer slurry separation plant BE170-60 with a flow capacity of 170 m³/h.

We offer ca compact Bauer slurry separation plant BE170-60.

Ideal for smal microtunnelling machines up to DN1000.

Due to the galvanised structure, those separation plants stay in a good condition.

For Sale & For Rent

capacity	m3/h	170
pump		6"
rotation speed	rpm	1,465
installed power		
pump motor	kW	30
vibrating screen motor	kW	2 x 2
voltage frequency	V/HZ	380/50 (220 /60 or 460/60)
cyclone		
diameter	mm	450
cut point d ₅₀	mm	0,060
sieve		
total sieve area	m2	2,4
coarse sieve		
sieve inclination	°	0 to +6°
mesh width	mm	5 x 25
sieve area	m2	1,2
dewatering sieve		
sieve inclination	°	0 to +6°
mesh width	mm	0,4 x 16
area	m2	1,2
weight	kg	4,150
dimensions	m	3,70 x 2,25
L x W x H		2,50

Microtunneling Bauer slurry separation plant BE170-60, fully serviced by manufacturer with warranty

